



Condensers

Rooftop condensers




Product overview and technical data

Model	Performance	Dimensions L x W x H	Specifications	Power consumption at 12 V (A)	Weight	Voltage	Part Number
Capri*							
	27,300 BTU/h (8 kW)	32.1 x 23.6 x 5.9 in (815 x 600 x 150 mm)	HTC condenser, fin pitch .14 in (3.5 mm), Integrated Receiver Dryer	18 A	26.5 lbs (12 kg)	12 V	62U00025430
	35,800 BTU/h (10.5 kW)		HTC condenser, fin pitch .1 in (2.5 mm), Integrated Receiver Dryer			12 V	62U00025456
Valencia*							
	42,650 BTU/h (12.5 kW)	37.6 x 23.6 x 5.9 in (955 x 600 x 150 mm)	HTC condenser, Integrated Receiver Dryer	27 A	31 lbs (14 kg)	12 V	62U00025437

* NOTE: This unit does not come with a pressure switch.

Under chassis condensers

Product overview and technical data

Model	Performance	Dimensions L x W x H	Specifications	Power consumption at 12 V (A)	Weight	Voltage	Part Number
HTC Condenser Units							
	17,000 BTU/h (5 kW)	23.9 x 4.3 x 13.8 in (606 x 110 x 350 mm)	fin pitch 0.14 in (3.5 mm)	18 A	9.9 lbs (4.5 kg)	12 V	62U00025427
	24,000 BTU/h (7 kW)		fin pitch 0.1 in (2.5 mm)				62U00025460
	22,200 BTU/h (6.5 kW)	18.9 x 4.3 x 13.8 in (480 x 110 x 350 mm)	fin pitch 0.1 in (2.5 mm)	12 A	8.2 lbs (3.7 kg)		62U00025453
	41,000 BTU/h (12 kW)	28.5 x 4.1 x 17.7 in (725 x 105 x 450 mm)	fin pitch 0.14 in (3.5 mm)	27 A	13.2 lbs (6 kg)		62U00025426
	47,800 BTU/h (14 kW)		fin pitch 0.1 in (2.5 mm)				62U00025459
	41,000 BTU/h (12 kW)	23.9 x 6.3 x 13.8 in (606 x 160 x 350 mm)	fin pitch 0.1 in (2.5 mm)	32 A	16.5 lbs (7.5 kg)		62U00025472